

for use with



ENVIRONMENTAL COATINGS

You may be familiar with the features of the Posi-Shell® Cover System:

- Easy to mix and apply.
- Useful for overnight cover and durable long-term cover.
- Use your own hydroseeding unit or lease an Applicator from us.

Now Xtreme Rain Shield™ makes

it more versatile than ever.



Visit www.LSCenv.com to read more stories of Xtreme Rain Shield™ success in Asia.

Call for more information.

Xtreme Rain Shield™ added to conventional Posi-Shell® mix produces a coating that resists massive rain events **IMMEDIATELY!**







for use with



ENVIRONMENTAL COATINGS





Brief Specifications:

- Powdered additive for Posi-Shell® products.
- Used when heavy rains are expected within 12 hours of application.
- Improves resistance to rain before cure.
- Improves adhesion to all surfaces.
- Proprietary blend of synthetic polymers.
- 100% biodegradable and non-toxic.
- Exposed methyl groups on the polymer chain absorb onto the surface of plate-like clay particles forming bonds that are not easily broken.
- Bulk Density: 28-32 lbs per cu. ft.
- Particle Size: 100% passes through 28 mesh screen

Contact us today for more information.

For technical services or to locate your nearest Xtreme Rain Shield™ dealer:



Call: 1-800-800-7671 • Email: Sales@LSCenv.com

Visit LSC online at: www.LSCenv.com
LSC Environmental Products, LLC

2183 Pennsylvania Ave., Apalachin, NY 13732



Information and statements herein are believed to be reliable but are not to be constructed as a warranty or guarantee. LSC Environmental Products, LLC offers no warranties, express or implied. Nothing herein is to be taken as permission to practice any patented invention without a license. Technology described herein may be covered by one or more patents or pending patent applications. See website for patent details Xtreme Rain Shield™ and Posi-Shell® are registered trademark of LSC Environmental Products, LLC. All rights reserved. © 2017 LSC Environmental Products, LLC